



AssureaKote™ COATED U-BOLT



Phone: 337-837-4141



AssureaKoteTM COATED U-BOLT

Overview

The AssureaKote™ coated u-bolt is versatile and can be used in many industries including but not limited to: pipelines, refineries, chemical plants, offshore platform, rigs, paper mills, and marine applications. Step-Ko Products keeps a wide variety of sizes of AssureaKote™ u-bolts in stock for immediate shipment in standardized box quantities.


Benefits

All the AssureaKote™ u-bolts in sizes 24" and below are packaged in a strong durable poly bag with the u-bolt, 4 nuts and a rubber pad for easy application in the field, eliminating the removal of the nuts from the u-bolt before applying to the piping, therefore eliminating unneeded labor time.

Features

Step-Ko Products' AssureaKote™ coating technology is a special proprietary coating that has superior temperature and physical properties when applied to various types of u-bolts. The AssureaKote[™] coating provides excellent protection from corrosion by preventing metal to metal contact between the ubolt and piping.








Nominal Pipe Size	Bolt Stock OD	U-Bolt Height "A"	Thread Length "B"	Inside Gap "C"	Leg Center "D"	Box Quantity
1"	1/4″	3 7/16"	2 3/8"	1 3/8"	1 5/8"	100 p/Box
1"	3/8″	3 7/16"	2 3/8"	1 3/8″	1 3/4″	100 p/Box
1-1/2"	3/8"	4"	2 1/2"	2″	2 3/8"	100 p/Box
2″	3/8″	4 1/2"	2 1/2"	2 7/16"	2 13/16"	100 p/Box
3″	1/2″	5 13/16"	3″	3 9/16"	4 1/16"	50 p/Box
4"	1/2″	6 13/16"	3″	4 9/16"	5 1/16"	50 p/Box
6″	5/8″	9 1/2"	3 3/4"	6 3/4"	7 3/8"	20 p/Box
8″	5/8″	11 1/2"	3 3/4"	8 3/4"	9 3/8"	15 p/Box
10"	3/4"	13 13/16"	4"	10 <i>7/</i> 8″	11 5/8″	15 p/Box
12"	7/8″	16 1/16"	4 1/4"	12 <i>7/</i> 8″	13 3/4"	10 p/Box
14"	7/8″	17 5/16"	4 1/4"	14 1/8″	15"	Available On Request
16"	7/8″	19 5/16"	4 1/4"	16 1/8"	17"	Available On Request
18"	1"	21 11/16"	4 3/4"	18 1/8″	19 1/8″	Available On Request
20″	1"	23 11/16"	4 3/4"	20 1/8"	21 1/8"	Available On Request
24"	1"	27 11/16"	4 3/4"	24 1/8"	25 1/8"	Available On Request
30″	1″	33 11/16"	4 3/4"	30 1/8″	31 1/8″	Available On Request
36"	1"	39 11/16"	4 3/4"	36 1/8"	37 1/8"	Available On Request



Phone: 337-837-4141 Email: info@stepko.com



AssureaPadTM





Properties	Value	Standard	
Physical			
Tensile Strength	2900 psi min. (19.9N/mm2)	ASTM D638	
Ultimate Elongation	350% min.	ASTM D638	
Density	1.24 +or2 gm/cm3	ASTM D792	
Durometer	92 +/-2 Shore A / 36+/-2 Shore D	ASTM D2240	
Tear Strength	470 pli min	ASTM D638	
Water Absoption	0.236% Average / 0.264% Max	ASTM D570-98	
Thermal			
Heat Age	120°C for 500 Hours No Cracking	ASTM D2671	
Aged Tensile	3639 psi (25 N/mm2)	ASTM D638	
Aged Elongation	300%	ASTM D638	
Low Temperature Flexability	4Hrs @ -40° C No Cracking	ASTM 2671-13	
Electrical			
Delectric Strength	490 V/mil min. (19 KV/mm Min.)	ASTM D149	
Volume Resistivity	5.55x 10 ^10 Ohm*cm	ASTM D257-14	
Dielectric Constant	0.72728 Average @ 20 Hz	ASTM D150-11	
	0.08100 Average @ 500 Hz	ASTM D150-11	

*Step-Ko's Flange Isolation Gasket kits are manufactured according to the AMPP (NACE) SP0286-2007 Standard to meet customer requirements to fit flange dimensions of ANSI, AWWA, MSS SP-44, B.S. 10, DIN2633, etc.



Step-Ko Coated U-bolt Advantages

- Step-Ko Products stocks hot dipped galvanized figure 137 long tangent u-bolts with AssureaKote™ and without AssureaKote™.
- AssureaKote[™] u-bolt is packaged with 4 nuts and a neoprene u-bolt pad.
- Step-Ko Products also has Stainless Steel, Electro Plated Galvanized, Teflon coated or Xylan Coated u-bolts available upon request.




Phone: 337-837-4141 Email: info@stepko.com



AssureaPadTM

AssureaPad Dimensions







Phone: 337-837-4141 Email: info@stepko.com



PROTECTING ASSETS FROM THE ENVIRONMENT

Other Product Offerings:

Flange Insulation Gasket Kits
Flange Protectors
Nut & Bolt Protectors
Heat Shrink Sleeves & Tapes
Solutions For Sealing Pipelines From Corrosion
Pipeline Pigs
Pipeline Markers & Test Stations
Insulated Enclosures/Buildings
Anodes

Distributor/Representative

337.837.4141
P.O. Box 81396 • Lafayette, LA 70598
www.stepko.com